

/// 5 AXLE 51,000L SINGLE COMPT SEMI-TRAILER WASTE WATER



Technical Specification	PS55106NA0RE		
Model & Regulations	Non-code, CMVSS 121 (Brakes); CMVSS 108 (Electrical); ONT 413/O5 SPIF	Wabco Brake Syst. CMVSS 121	16.5 x 7 ABS 4S/2M RSS Plus on Tridem Axle ABS 2S/1M per Lift Steer Axles
Capacity & Compt	51,000L, 1 Compartment Double Bulkheads w/ Baffles per Design	Air Tanks & Wiring	All Aluminum Air Tanks per Design Colour-Coded Air Lines per SAE Std
Tank Outer Shell Tank Framing	5454 H32 Alloy BTS Finish Alum Crossmembers & Outriggers per design	KP Plate	Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes
Manholes	One (1) Betts 20" PPVL720BXT with 10" opening Two (2) 20" inspection manholes	Landing Gear	Holland Mark V 200,000 LBS Two Speed w/ Non-Removeable Handle
Suspension Frame	Heavy Duty HLSA Steel Suspension Frame w/ Brackets for Huck Bolt-On Installation	Paint	Susp Frame & Hangers Powder Coat Black Axle Tectyl Coat, LG Black Armour Coat
Suspension Tridem Axle	HENDRICKSON INTRAXX RH HXL-3 PKG AAT25K-14" 25,000 LBS Capacity, Bolt-On Style	Electrical & Lighting Systems CMVSS 108	Fully Certified Electrical and Lighting Systems. Truck-Lite LED Lighting PKG
Suspension Lift & Self- Steer Axles (2)	Ingersol IMT-25K-14" TLS; 25,000 LBS Capacity w/ Lift & Self Steer PKG	Aluminum Cabinets	One (1) 48" Installed Curbside
Hub & Drums for All Suspensions	Conmet Unimount ADI Hubs w/ Outboard (Centrifuse) Brake Drums; Tiremaax Prep	Other Accessories	Aluminum Fenders; Aluminum Ladder
Tridem Axle Wheels & Tires	8.25 x 22.5 Std Aluminum Wheels Michelin XTE 11R 22.5 14(G)	Documents	All Documents Completed & Provide to Customer
Lift & Steer Wheels & Tires	12.25 x 22.5 Std Aluminum Wheels Michelin X-Multiway HD L385/65R 22.5		