

**/// 4 AXLE 57,000L MULTI-COMPT TC 406 SEMI-TRAILER**



<b>Technical Specification</b>	PS45706NA6RE		
<b>Model &amp; Regulations</b>	TC 406; ASME; CSA B620; CMVSS 121 (Brakes); CMVSS 108 (Electrical); ONT 413/O5 SPIF	<b>Hub &amp; Drums for All Suspensions</b>	Conmet Unimount ADI Hubs w/ Outboard (Centrifuse) Brake Drums; Tiremaax Prep
<b>Capacity &amp; Compt</b>	57,000L; 4, 5 & 6 Compartment Trailers; Double Bulkheads w/ Baffles per Design	<b>Tridem Axle Wheels &amp; Tires</b>	8.25 x 22.5 Std Aluminum Wheels; Michelin XTE 11R 22.5 14(G)
<b>Tank Outer Shell; Tank Framing</b>	5454 H32 Alloy BTS Finish; Alum Crossmembers & Outriggers per design	<b>Lift &amp; Steer Wheels &amp; Tires</b>	12.25 x 22.5 Std Aluminum Wheels; Michelin X-Multiway HD L385/65R 22.5
<b>SUPER TANKER PKG Extended Warranty</b>	SUPERTANKER 5 YEAR Limited Warranty on Dixon, Betts & FloTech Components	<b>Wabco Brake Syst. CMVSS 121</b>	16.5 x 7 ABS 4S/2M RSS Plus on Tridem Axle; ABS 2S/1M per Lift Steer Axles
<b>Manholes; Vents</b>	Betts 20" 406-98 PAF Relief Manholes , Betts AVT 3.5" ALTS Sequential Air Vapor Vents	<b>Air Tanks &amp; Wiring</b>	All Aluminum Air Tanks per Design; Colour-Coded Air Lines per SAE Std
<b>Overfill Protection</b>	FloTech Optic Top & Retain Sensors per Compt W/ On Board Monitor	<b>KP Plate</b>	Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes
<b>Emergency Valves &amp; Discharge System</b>	Betts 4" Air Internal Valves w/ Tef-Sil Seals Dixon 4" API Adaptors w/ Baylast Seals	<b>Landing Gear</b>	Holland Mark V 200,000 LBS Two Speed w/ Non-Removeable Handle
<b>Vapour Recovery Syst. Loading &amp; Unloading</b>	Three 3" Vapour API w/ Poppets; 1 at Rear of for Loading, 2 at Discharge Area for Unloading	<b>Paint</b>	Susp Frame & Hangers Powder Coat Black; Axle Tectyl Coat, LG Black Armour Coat
<b>Piping System</b>	4" Seamless Alum Sch 10 High Flow Piping Formed & Bent with Minimum Welding	<b>Electrical &amp; Lighting Systems CMVSS 108</b>	Fully Certified Electrical and Lighting Systems. Truck-Lite LED Lighting PKG
<b>Suspension Frame</b>	Heavy Duty HLSA Steel Suspension Frame w/ Brackets for Huck Bolt-On Installation	<b>Aluminum Cabinets</b>	42" Curbside Utility Cabinet; 48" Curbside Operation Cabinet
<b>Suspension Tridem Axle</b>	HENDRICKSON INTRAXX RH HXL-3 PKG AAT25K-14" 25,000 LBS Capacity, Bolt-On Style	<b>Other Accessories</b>	Aluminum Fenders; Aluminum Ladder; Aluminum Hose Tubes & More
<b>Suspension Lift &amp; Self-Steer Axles (1)</b>	Ingersol IMT-25K-14" TLS; 25,000 LBS Capacity w/ Lift & Self Steer PKG	<b>Documents</b>	All Test & Certifications Documents Completed & Provide to the Customer